

# 06 Washdown Pumps



## PAR-Max Washdown Kit



Jabco offers boaters several washdown pumps at ideal flow and pressure for washdown. Washdown pumps are ideal for cleaning decks, cockpits and anchors on yachts of a range of sizes and can be connected to sea or fresh water. Both units come with an intake strainer, spray nozzle and quick-connect 3/4" (19mm) hose barb fittings.

- High pressure jet blasts mud and silt from anchor chain and decks.
- Waterproof with sealed motor and sealed pressure switch for mounting in exposed positions.
- Thermal overload protection automatically stops the motor if it overheats.
- Dry running.
- Soft rubber mounts.
- Corrosion resistant.
- Complies with USCG 183.410 and ISO 8846 MARINE (Ignition Protection).
- Supplied complete with Pumpgard™ and trigger nozzle.

| MODEL      | DESCRIPTION   |
|------------|---|
| 30703-1000 | Quick-Disconnect Nozzle with 3/4" (19mm) GHT snap-in connector.                       |
| 30704-1000 | Quick-Disconnect Nozzle attaches permanently to 1/2" (13mm) hose.                     |
| 46400-0000 | Pumpgard™ Strainer for North America  |
| 46400-0002 | Pumpgard™ Strainer for Europe   |
| 31911-0000 | Deck Fitting, 1/2" (13mm) NPT female inlet with one 3/4" (19mm) GHT male hose adapter |
| 31911-0007 | Deck Fitting, 1/2" (13mm) BSP female inlet with one 3/4" (19mm) BSP male hose adapter |
| 31911-0002 | Hose Adapter  |

## PAR-Max 3.0 GPM Washdown Pump

- Suitable for marine washdown.
- Self-priming up to 10' (3m).

Included



|                          |  |
|--------------------------|--|
| <b>FLOW</b>              | 3.0 GPM (11.4 LPM)   |
| <b>SHUT-OFF PRESSURE</b> | 50 psi (3.5 bar)   |
| <b>FITTING</b>           | Connections for 3/4" (19mm) straight hose barb               |
| <b>SIZE</b>              | 9" long x 4.24" wide x 4.75" high (22.9cm x 10.6cm x 12.1cm) |
| <b>WEIGHT</b>            | 3.5lb (1.6kg)  |

| MODEL      | DESCRIPTION   |
|------------|---|
| 32305-0092 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 32305-0094 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 32305-0392 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 32305-0394 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 32901-0092 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil |
| 32901-0094 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil  |

## PAR-Max 4.0 GPM Washdown Pump

- Suitable for high pressure applications
- Self-priming up to 10' (3m).

Included



|                          |  |
|--------------------------|--|
| <b>FLOW</b>              | 4.0 GPM (15 LPM)   |
| <b>SHUT-OFF PRESSURE</b> | 60 psi (4 bar)   |
| <b>FITTING</b>           | Connections for 3/4" (19mm) ID hose                          |
| <b>SIZE</b>              | 9" long x 4.24" wide x 4.75" high (22.9cm x 10.6cm x 12.1cm) |
| <b>WEIGHT</b>            | 5lb (2.1kg)  |

| MODEL      | DESCRIPTION   |
|------------|---|
| 32605-0092 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 32605-0094 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 32605-0392 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 32605-0394 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 32900-0092 | 12V DC, fuse 10 amp, 4.4 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil |
| 32900-0094 | 24V DC, fuse 5 amp, 2.2 amp draw @ 10 psi, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil  |

## HotShot Series



Robust five chamber, patented co-injected molded diaphragm and larger heavy-duty motor brushes significantly extend pump life by up to 50%. The HotShot Series Washdown Pumps are available in 4.0 GPM (15.1 LPM), 5.0 GPM (18.9 LPM) and 6.0 GPM (22.7 LPM) with pressures up to 70 psi (4.8 bar) and are self-priming up to 10' (3m).

- Sealed switch and co-molded diaphragm eliminates leak paths, extending the life of the pump by up to 50%.
- Ergonomically designed spray nozzle provides powerful and accurate fire power with every shot.
- Quick-disconnect ports allow for adjustability and ease of installation.
- Kits include spray nozzle, fitting, Pumpgard™ strainer and hose.
- Improved noise dampening rubber feet significantly minimize vibration when mounted against hard surfaces.
- Available in 12V or 24V DC.
- Certified to EN ISO 8846 Marine (Ignition Protection).

|                          |  |
|--------------------------|--|
| <b>FLOW</b>              | 4.0 GPM (15 LPM), 5.0 GPM (18.9 LPM) or 6.0 GPM (22.7 LPM)   |
| <b>SHUT-OFF PRESSURE</b> | 70 psi (4.8 bar)   |
| <b>FITTING</b>           | Connections for 3/4" (19mm) straight hose barb   |
| <b>SIZE</b>              | 4.0 GPM: 9.91" long x 5.09" wide x 4.34" high (25.2cm x 12.9cm x 11.1cm)<br>5.0 and 6.0 GPM: 10.6" long x 5.09" wide x 4.34" high (26.9cm x 12.9cm x 11.1cm) |
| <b>WEIGHT</b>            | 4.0 GPM: 7.6lb (3.5kg)<br>5.0 and 6.0 GPM: 7.6lb (3.5kg)   |

### 4.0 GPM MODELS

| MODEL      | DESCRIPTION   |
|------------|---|
| 82405-0092 | 12V DC, fuse 20 amp, 13 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 82405-0094 | 24V DC, fuse 15 amp, 7 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 82904-0092 | 12V DC, fuse 20 amp, 13 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil |
| 82904-0094 | 24V DC, fuse 15 amp, 7 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil  |

### 5.0 GPM MODELS

| MODEL      | DESCRIPTION   |
|------------|---|
| 82505-0092 | 12V DC, fuse 20 amp, 16 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 82505-0094 | 24V DC, fuse 15 amp, 8 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 82905-0092 | 12V DC, fuse 20 amp, 16 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil |
| 82905-0094 | 24V DC, fuse 15 amp, 8 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil  |

### 6.0 GPM MODELS

| MODEL      | DESCRIPTION   |
|------------|---|
| 82605-0092 | 12V DC, fuse 25 amp, 18 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                       |
| 82605-0094 | 24V DC, fuse 15 amp, 9 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle                        |
| 82906-0092 | 12V DC, fuse 25 amp, 18 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil |
| 82906-0094 | 24V DC, fuse 15 amp, 9 amp draw maximum, two 3/4" (19mm) straight hose barbs, strainer, nozzle, 25' (7.6m) hose coil  |